

346015 Woodura Planks LYA 3.0 XL

Generelt

Type gulv	Herdet tregulv
Treslag	Eik
Sortering	Select
Overflatebehandling	Børstet mattlakk
Innfarging	Natural
Lyst/mørkt	Halvmørkt
Mønster	Plank
Fug	Välinge 5G(R) Dry(TM)
Kjerne	HDF
Mikrobevel	4 sided

Mål

Format	XL
Bredde	206 mm
Lengde	2200 mm
Høyde	11,3 mm
Slitesjiktets tykkelse	0,6 mm

Emballasje

Antall i pakken	4 stk.
m² i pakken	1,81 m²
m² per pall	87 m²
Vekt pr. m2	11 kg
Vekt pr. pakke	20 kg

Klassifisering og sikkerhet

Egnet for gulvvarme	Ja
Vannbestandighet	Høy
Motstandsyktighet mot brann (EN 13501)	Bfl-S1 (Begrenset brennbart)
Termisk ledningsevne (EN 12664)	0,16 W/(m*K)
Termisk motstand (EN 12667)	0,07 m²K/W
Formaldehyd emisjon (EN 717-1)	E1<=0,124 mg/m3
Brinellhardhet (EN 1534)	8 HB (average value)
Slagfasthet (EN 14354)	EC3
Svellingsgrad (EN 14354)	<10% (5% type verdi)
Slitestyrke (EN 14354)	> 1000 cycles
FSC	FSC Mix
SundaHus	Bedømt av SundaHus
Svanen	Ja (3029 0021)
Greenguard Gold	Greenguard Gold Certified
CE-merket	Ja
Garanti (offentlige miljø)	30 år
Garanti (private hjem)	30 år
Slitestyrke i private hjem (EN ISO 10874)	Moderat trafikkerte områder i hjemmemiljøet (Klasse 22)
Annen	
NOBB-nummer	60085988

Skann QR-koden med mobilen eller besøk bjelin.com for å se informasjon om legging og ytterligere produktinformasjon.



woodura® Licensed by Välinge

Bjelin support@bjelin.com +47 3322 2300

Copyright 2024 Bjelin Innovation. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Woodura and 5G Dry are patented technologies invented by Välinge Innovation AB. The logos are trademarks owned by Välinge Innovation AB and authorized use of such marks are under license.