

347058 Woodura Planks SMEDSTORP 3.0 XL

Generelt

Type gulv	Herdet tregulv
Treslag	Ask
Sortering	Select
Overflatebehandling	Pro matt lacquer
Innfarging	Earth Grey
Lyst/mørkt	Lyst
Mønster	Plank
Fug	Välinge 5G(R) Dry(TM)
Kjerne	HDF

Mål

Format	XL
Bredde	206 mm
Lengde	2200 mm
Høyde	11,3 mm
Slitesjiktets tykkelse	0,6 mm

Emballasje

Antall i pakken	4 stk.
m² i pakken	1,81 m²
m² per pall	87 m²
Vekt pr. m2	11 kg
Vekt pr. pakke	20 kg

Klassifisering og sikkerhet

Egnet for gulvvarme	Ja
Vannbestandighet	Høy
Motstandsyktighet mot brann (EN 13501)	Bfl-S1 (Begrenset brennbart)
Termisk ledningsevne (EN 12664)	0,16 W/(m*K)
Termisk motstand (EN 12667)	0,07 m²K/W
Formaldehyd emisjon (EN 717-1)	E1 <=0,1 ppm (type verdi <= 0,05 ppm)
Brinellhardhet (EN 1534)	10 HB (average value)
Slagfasthet (EN 14354)	EC3
Svellingsgrad (EN 14354)	<10% (5% type verdi)
Slitestyrke (EN 14354)	> 6000 cycles
Sklisikkerhet (USRV) (CEN//TS 15676)	40
FSC	FSC Mix
Greenguard Gold	Greenguard Gold Certified
CE-merket	Ja
Garanti (offentlige miljø)	30 år
Garanti (private hjem)	30 år
Slitestyrke i private hjem (EN ISO 10874)	Moderat til sterkt trafikkerte områder (klasse 23)
Slitestyrke i offentlige miljø (EN ISO 10874)	Høytrafikkområder (klasse 33)
Annen	
NOBB-nummer	60085996

Skann QR-koden med mobilen eller besøk bjelin.com for å se informasjon om legging og ytterligere produktinformasjon.



woodura®



Bjelin support@bjelin.com +47 3322 2300

Copyright 2024 Bjelin Innovation. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Woodura and 5G Dry are patented technologies invented by Välinge Innovation AB. The logos are trademarks owned by Välinge Innovation AB and authorized use of such marks are under license.