

347066 Woodura Planks VISTORP 3.0 XL



Generelt

| | |
|---------------------|-----------------------|
| Type gulv | Herdet tregulv |
| Treslag | Eik |
| Sortering | Select |
| Overflatebehandling | Pro matt lacquer |
| Innfarging | Powder White |
| Lyst/mørkt | Lyst |
| Mønster | Plank |
| Fug | Vålinge 5G(R) Dry(TM) |
| Kjerne | HDF |

Mål

| | |
|------------------------|---------|
| Format | XL |
| Bredde | 206 mm |
| Lengde | 2200 mm |
| Høyde | 11,3 mm |
| Slitesjiktets tykkelse | 0,6 mm |

Emballasje

| | |
|-------------------------|---------------------|
| Antall i pakken | 4 stk. |
| m ² i pakken | 1,81 m ² |
| m ² per pall | 87 m ² |
| Vekt pr. m2 | 11 kg |
| Vekt pr. pakke | 20 kg |

Klassifisering og sikkerhet

| | |
|---|--|
| Egnet for gulvvarme | Ja |
| Vannbestandighet | Høy |
| Motstandsyktighet mot brann (EN 13501) | Bfl-S1 (Begrenset brennbart) |
| Termisk ledningsevne (EN 12664) | 0,16 W/(m*K) |
| Termisk motstand (EN 12667) | 0,07 m ² K/W |
| Formaldehyd emisjon (EN 717-1) | E1 <=0,1 ppm (type verdi <= 0,05 ppm) |
| Brinellhardhet (EN 1534) | 10 HB (average value) |
| Slagfasthet (EN 14354) | EC3 |
| Svellingsgrad (EN 14354) | <10% (5% type verdi) |
| Slitestyrke (EN 14354) | > 6000 cycles |
| Sklisikkerhet (USRV) (CEN//TS 15676) | 40 |
| FSC | FSC Mix |
| SundaHus | Bedømt av SundaHus |
| Svanen | Ja (3029 0021) |
| Greenguard Gold | Greenguard Gold Certified |
| CE-merket | Ja |
| Garanti (offentlige miljø) | 30 år |
| Garanti (private hjem) | 30 år |
| Slitestyrke i private hjem (EN ISO 10874) | Moderat til sterkt trafikkerte områder (klasse 23) |
| Slitestyrke i offentlige miljø (EN ISO 10874) | Høytrafikkområder (klasse 33) |

Annen

| | |
|-------------|----------|
| NOBB-nummer | 60085943 |
|-------------|----------|



Bjelin support@bjelin.com +47 3322 2300

Copyright 2024 Bjelin Innovation. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Woodura and 5G Dry are patented technologies invented by Välinge Innovation AB. The logos are trademarks owned by Välinge Innovation AB and authorized use of such marks are under license.