

347102 Woodura Planks HASLARP 3.0 XXL



Generelt	
Type gulv	Herdet tregulv
Treslag	Eik
Sortering	Nature
Overflatebehandling	Pro matt lacquer
Innfarging	Misty White
Lyst/mørkt	Lyst
Mønster	Plank
Fug	Vålinge 5G(R) Dry(TM)
Kjerne	HDF
Mål	
Format	XXL
Bredde	271 mm
Lengde	2378 mm
Høyde	11,3 mm
Slitesjiktets tykkelse	0,6 mm
Emballasje	
Antall i pakken	3 stk.
m ² i pakken	1,9 m ²
m ² per pall	93 m ²
Vekt pr. m2	11 kg
Vekt pr. pakke	22 kg
Klassifisering og sikkerhet	
Egnet for gulvvarme	Ja
Vannbestandighet	Høy
Motstandsyktighet mot brann (EN 13501)	Bfl-S1 (Begrenset brennbart)
Termisk ledningsevne (EN 12664)	0,16 W/(m*K)
Termisk motstand (EN 12667)	0,07 m ² K/W
Formaldehyd emisjon (EN 717-1)	E1 <=0,1 ppm (type verdi <= 0,05 ppm)
Brinellhardhet (EN 1534)	10 HB (average value)
Slagfasthet (EN 14354)	EC3
Svellingsgrad (EN 14354)	<10% (5% type verdi)
Slitestykke (EN 14354)	> 6000 cycles
Sklisikkerhet (USRV) (CEN//TS 15676)	40
FSC	FSC Mix
SundaHus	Bedømt av SundaHus
Svanen	Ja (3029 0021)
Greenguard Gold	Greenguard Gold Certified
CE-merket	Ja
Garanti (offentlige miljø)	30 år
Garanti (private hjem)	30 år
Slitestykke i private hjem (EN ISO 10874)	Moderat til sterkt trafikkerte områder (klasse 23)
Slitestykke i offentlige miljø (EN ISO 10874)	Høytrafikkområder (klasse 33)

Annen	
NOBB-nummer	60085923

Skann QR-koden med mobilen eller besøk bjelin.com for å se informasjon om legging og ytterligere produktinformasjon.



Bjelin support@bjelin.com +47 3322 2300

Copyright 2024 Bjelin Innovation. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Woodura and 5G Dry are patented technologies invented by Välinge Innovation AB. The logos are trademarks owned by Välinge Innovation AB and authorized use of such marks are under license.